

## Stock Perforated Weights

This Technical Data Sheets provides the weights per sheet for Locker Group's stock perforated metal profiles

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
<b>ROUND HOLES</b>								
R530	0.75	1.2	35%	St/St 304	0.45	2100 x 915	141	4.61
R00520S403C2	0.5	1.07	20%	St/St 304	0.3	Coil x 610	668	1.20 (l/m)
R00831MS0663	0.81	1.4	31%	Mild Steel	0.6	1830 x 915	131	5.27
R535	1.00	1.5	40%	St/St 304	0.5	4200 X 915	64	9.38
R01 025S405C3	1.02	1.93	25%	St/St 304	0.45	Coil x 915	297	2.53 (l/m)
R01623MS12	1.60	3.20	23%	Mild Steel	1.20	2440 x 1220	36	21.39
R01636GB0873	1.60	2.54	36%	Galvanised	0.80	2050 x 915	82	7.80
R01636MS08	1.60	2.54	36%	Mild Steel	0.80	2440 x 1220	53	12.08
R01636S407	1.60	2.54	36%	St/St 304	0.70	2440 x 1220	59	10.85
R01637GB08	1.60	2.50	37%	Galvanised	0.80	2440 x 1220	52	12.12
R01637GB10	1.60	2.50	37%	Galvanised	1.00	2440 x 1220	41	15.37
R01637MS10	1.60	2.50	37%	Mild Steel	1.00	2440 x 1220	43	14.65
R01637S40763	1.60	2.54	36%	St/St 304	0.70	1830 x 915	108	5.93
R01637ZS06	1.60	2.50	37%	Zinc Seal	0.55	2440 x 1220	75	9.00
R01637ZS08	1.60	2.50	37%	Zinc Seal	0.80	2440 x 1220	53	11.89
R01637ZS0864	1.60	2.50	37%	Zinc Seal	0.80	1830 x 1220	70	9.00
R02036ZS06	1.95	3.10	36%	Zinc Seal	0.55	2440 x 1220	75	9.14
R02040GB10	2.00	3.00	40%	Galvanised	1.00	2440 x 1220	41	14.63
R02040MS10	2.00	3.00	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R02141S409	2.06	3.10	41%	St/St 304	0.90	2440 x 1220	46	12.83
R02141ZS05	2.06	3.10	41%	Zinc Seal	0.50	2440 x 1220	85	6.94
RMEATSAFE	2.06	3.10	41%	Zinc Seal	0.55	2440 x 1220	85	6.94
<b>ACOUSTIC PATTERN</b>								
R02411A50683	2.41	9.55	10%	Aluminium	0.55	2400 x 900	285	3.16
R02411A508	2.38	6.74	11%	Aluminium	0.80	2400 x 1200	160	5.56
R02411GB06	2.38	6.74	11%	Galvanised	0.55	2440 x 1220	75	11.87
R02411GB06103	2.38	6.74	11%	Galvanised	0.55	3050 x 915	80	11.13
R02411GB06104	2.38	6.74	11%	Galvanised	0.55	3050 x 1220	60	14.83
R02411GB06105	2.38	6.74	11%	Galvanised	0.55	3000 x 1500	49	18.16
R02411GB0663	2.38	6.74	11%	Galvanised	0.55	1830 x 915	133	6.69

- This information is provided as a guide only in respect to Locker Group products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Locker Group endeavors to update this information and maintain the accuracy of its content, Locker Group cannot guarantee that the information provided is wholly comprehensive

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R02411GB0664	2.38	6.74	11%	Galvanised	0.55	1830 x 1220	100	8.90
R02411GB0683	2.38	6.74	11%	Galvanised	0.55	2440 x 915	100	8.90
R02411GB0685	2.38	6.74	11%	Galvanised	0.55	2440 x 1500	61	14.59
R02411GB06C4	2.38	6.74	11%	Galvanised	0.55	1 L/M x 1220	178	5.00
R02411GB06C5	2.38	6.74	11%	Galvanised	0.55	1 L/M x 1500	149	5.97
R02411GB06C5-170	2.41	9.55	10%	Galvanised	0.55	170 l/m x 1500	149	5.30 (l/m)
R02411GB08	2.38	6.74	11%	Galvanised	0.80	2440 x 1220	52	17.12
R02411S406	2.38	6.74	11%	St/St 304	0.55	2440 x 1220	75	11.87
R02411ZA06	2.38	6.74	11%	Zinc Anneal	0.55	2440 x 1220	75	12.71
R02411ZA06C4	2.41	9.55	10%	Zinc Anneal	0.55	170 l/m x 1200	170	5.30 (l/m)
R02411ZA06C4	2.38	6.74	11%	Zinc Anneal	0.55	1 L/M x 1220	187	4.77 (l/m)
R02411ZA08	2.38	6.74	11%	Zinc Anneal	0.55	1 L/M x 1220	187	4.77 (l/m)
R02411ZS05	2.38	6.74	11%	Zinc Seal	0.80	2440 x 1220	53	16.79
				Zinc Seal	0.53	2440 x 1220	78	11.41
<b>ROUND HOLES</b>								
R02440A50683	2.41	3.66	40%	Aluminium	0.60	2400 x 900	128	4.69
R02440A510	2.41	3.66	40%	Aluminium	1.00	2400 x 1200	128	4.69
R02440A51263	2.38	3.57	40%	Aluminium	1.20	1800 X 900	190	3.16
R02440GB10	2.38	3.57	40%	Galvanised	1.00	2440 x 1220	41	14.63
R02440GB16	2.38	3.57	40%	Galvanised	1.60	2440 x 1220	26	23.08
R02440MS06	2.41	3.66	40%	Mild Steel	0.60	2440 x 1220	70	8.57
R02440MS10	2.38	3.57	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R02440MS16	2.38	3.57	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R02440S409	2.38	3.57	40%	St/St 304	0.90	2440 x 1220	46	13.04
R02440S609	2.38	3.57	40%	St/St 316	0.90	2440 x 1220	46	13.04
R03230A51063	3.17	5.56	30%	Aluminium	1.00	1800 x 900	228	3.07
R03230A516	3.17	5.56	30%	Aluminium	1.60	2400 x 1200	80	8.75
R03230GB06	3.17	5.56	30%	Galvanised	0.55	2440 x 1220	70	10.00
R03230GB06C4	3.17	5.56	30%	Galvanised	0.55	1 L/M x 1220	178	3.94 (l/m)
R03230GB08	3.17	5.56	30%	Galvanised	0.80	2440 x 1220	51	13.73
R03230GB10	3.17	5.56	30%	Galvanised	1.00	2440 x 1220	41	17.07
R03230GB16	3.17	5.56	30%	Galvanised	1.60	2440 x 1220	26	26.92
R03230MS10	3.17	5.56	30%	Mild Steel	1.00	2440 x 1220	43	16.28
R03230MS16	3.17	5.56	30%	Mild Steel	1.60	2440 x 1220	27	25.93
R03230MS30	3.17	5.56	30%	Mild Steel	3.00	2440 x 1220	14	50.00
R03230S409	3.17	5.56	30%	St/St 304	0.90	2440 x 1220	46	15.22
R03230S415	3.17	5.56	30%	St/St 304	1.50	2440 x 1220	27	25.93
R03230S41563	3.17	5.56	30%	St/St 304	1.50	1830 x 915	27	25.93
R03230S612	3.25	5.59	30%	St/St 316	1.20	2440 x 1220	34	20.59
	3.17	5.56	30%					

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R03230S615	3.17	5.56	30%	St/St 316	1.50	2440 x 1220	27	25.93
R03230ZA06	3.17	5.56	30%	Zinc Anneal	0.55	2440 x 1220	70	10.00
R03230ZA10	3.17	5.56	30%	Zinc Anneal	1.00	2440 x 1220	41	17.07
R03240A506	3.24	4.78	40%	Aluminium	0.60	2400 x 1200	214	2.80
R03240GB06	3.17	4.76	40%	Galvanised	0.55	2440 x 1220	70	8.57
R03240GB08	3.17	4.76	40%	Galvanised	0.80	2440 x 1220	51	11.76
R03240GB10	3.17	4.76	40%	Galvanised	1.00	2440 x 1220	41	14.63
R03240GB16	3.17	4.76	40%	Galvanised	1.60	2440 x 1220	26	23.08
R03240MS08	3.17	4.76	40%	Mild Steel	0.80	2440 x 1220	53	11.32
R03240MS10	3.17	4.76	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R03240MS12	3.17	4.76	40%	Mild Steel	1.20	2440 x 1220	36	16.67
R03240MS16	3.17	4.76	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R03240MS25	3.17	4.76	40%	Mild Steel	2.50	2440 x 1220	18	33.33
R03240MS30	3.17	4.76	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R03240S409	3.17	4.76	40%	St/St 304	0.90	2440 x 1220	46	13.04
R03240S415	3.17	4.76	40%	St/St 304	0.90	1830 x 915	84	7.14
<b>R03240S612</b>	3.17	4.76	40%	St/St 304	1.50	2440 x 1220	27	22.22
R03240ZA1264	3.17	4.76	40%	St/St 316	1.20	2440 x 1220	34	17.65
R03246S40963	3.25	4.78	40%	Zinc Anneal	1.20	1861 X 1220	50 PACK	
R03246ZS0644	3.25	4.52	46%	St/St 304	0.90	1830 X 915	84	6.43
R03325MS30	3.25	4.52	46%	Zinc Seal	0.55	934 X 900	200 pack	
R03341MS20	3.25	6.10	25%	Mild Steel	3.00	2440 x 1220	14	53.57
	3.25	4.78	41%	Mild Steel	2.00	2440 x 1220	21	28.10
	3.25	4.78	41%	Mild Steel	3.00	2500 x 1200	14	42.14
R03341MS3025001200	3.25	4.76	42%	St/St 316	1.50	1830 x 915	49	11.84
R03342S61563	3.25	4.52	46%	Mild Steel	1.00	2440 x 1220	43	12.56
R03346MS10	3.25	4.52	46%	St/St 304	0.90	2440 x 1220	46	11.74
R03346S409	3.97	5.59	46%	Mild Steel	1.60	2440 x 1220	27	20.00
R04046MS16	4.76	7.92	33%	Mild Steel	1.60	2440 x 1220	27	24.81
R04833MS16	4.76	7.92	33%	Mild Steel	3.00	2440 x 1220	14	47.86
R04833MS30	4.76	6.35	51%	Aluminium	1.00	2400 x 1200	128	3.83
R04851A510	4.76	6.35	51%	Aluminium	1.20	2400 x 1200	107	4.58
R04851A512	4.76	6.35	51%	Aluminium	1.60	2400 x 1200	80	6.13
R04851A516	4.76	6.35	51%	Galvanised	0.55	2440 x 1220	70	7.00
R04851GB06	4.76	6.35	51%	Galvanised	1.00	2440 x 1220	41	11.95
R04851GB10	4.76	6.35	51%	Galvanised	1.60	2440 x 1220	26	18.85
R04851GB16	4.76	6.35	51%	Mild Steel	1.00	2440 x 1220	43	11.40
R04851MS10	4.76	6.35	51%	Mild Steel	1.20	2440 x 1220	36	13.61
R04851MS12	4.76	6.35	51%	Mild Steel	1.60	2440 x 1220	27	18.15

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R04851MS20	4.76	6.35	51%	Mild Steel	2.00	2440 x 1220	22	22.27
R04851MS30	4.76	6.35	51%	Mild Steel	3.00	2440 x 1220	14	35.00
R04851MS3063	4.76	6.35	51%	Mild Steel	3.00	1830 x 915	25	19.60
R04851MS50	4.76	6.35	51%	Mild Steel	5.00	2400 x 1200	8	61.25
R04851S409	4.76	6.35	51%	St/St 304	0.90	2440 x 1220	46	10.65
R04851S40963	4.76	6.35	51%	St/St 304	0.90	1830 X 915	84	5.83
R04851S415	4.76	6.35	51%	St/St 304	1.50	2440 x 1220	27	18.15
R04851S41563	4.76	6.35	51%	St/St 304	1.50	1830x 915	50	9.80
R04851S615	4.76	6.35	51%	St/St 316	1.50	2440 x 1220	27	18.15
R04851ZA10	4.76	6.35	51%	Zinc Anneal	1.00	2440 x 1220	43	11.40
R04851ZU10	4.76	6.35	51%	Zinc Alume	1.00	2440 x 1220	43	11.40
	4.76	6.35	51%	Zinc Alume	1.00	200LM x 1220	200	2.45 (l/m)
	6.35	9.53	40%	Galvanised	1.60	2440 x 1220	26	23.08
R04851ZU10C4-200	6.35	9.53	40%	Mild Steel	1.20	2440 x 1220	36	16.67
R06440GB16	6.35	9.53	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R06440MS12	6.35	9.53	40%	Mild Steel	2.50	2440 x 1220	18	33.33
R06440MS16	6.35	9.53	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R06440MS25	6.35	9.53	40%	Mild Steel	5.00	2400 x 1200	9	66.67
R06440MS30	6.35	9.53	40%	Mild Steel	6.00	2400 x 1200	7	85.71
<b>R06440MS50</b>	6.35	9.53	40%	St/St 304	1.50	2440 x 1220	27	22.22
R06440MS60	6.35	9.55	40%	St/St 304	1.50	1830 X 915	50	12.00
R06440S415	6.35	9.55	40%	Mild Steel	1.00	2440 x 1220	43	12.56
R06440S41563	6.35	8.89	46%	Aluminium	2.00	2400 x 1200	64	7.66
R06446MS10	6.35	8.50	51%	Galvanised	1.00	2440 x 1220	41	11.95
R06451A520	6.35	8.50	51%	Galvanised	1.60	2440 x 1220	26	18.85
R06451GB10	6.35	8.50	51%	Mild Steel	1.00	2440 x 1220	43	11.40
R06451GB16	6.35	8.50	51%	Mild Steel	1.20	2440 x 1220	36	13.61
R06451MS10	6.35	8.50	51%	Mild Steel	1.60	2440 x 1220	27	18.15
R06451MS12	6.35	8.50	51%	Mild Steel	3.00	2440 x 1220	14	35.00
R06451MS16	6.35	8.50	51%	St/St 304	0.90	2440 x 1220	46	10.65
R06451MS30	6.35	8.50	51%	St/St 304	0.90	1830 X 915	27	18.15
R06451S409	6.35	8.50	51%	St/St 304	1.50	2440 x 1220	27	18.15
R06451S40963	6.35	8.50	51%	St/St 304	1.50	1830 X 915	50	9.80
R06451S415	6.35	8.50	51%	Galvanised	1.60	2440 x 1220	26	14.62
R06451S41563	7.94	9.55	62%	Mild Steel	1.60	2440 x 1220	27	14.07
R07962GB16	7.94	9.55	62%	Mild Steel	2.00	2440 x 1220	21	18.10
R07962MS16	7.94	9.55	62%	Galvanised	1.00	2440 x 1220	42	12.62
R07962MS20	7.94	9.55	62%	Galvanised	1.60	2440 x 1220	26	20.38
R08047GB1 0	8.00	11.11	47%	Mild Steel	1.00	2440 x 1220	41	12.93
R08047GB1 6	8.00	11.11	47%					
R08047MS1 0	8.00	11.11	47%					

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R08047MS16	8.00	11.11	47%	Mild Steel	1.60	2440 x 1220	27	19.63
R08047MS30	8.00	11.11	47%	Mild Steel	3.00	2440 x 1220	14	37.86
R09523MS100	9.53	19.05	23%	Mild Steel	10.00	2400 x 1200	4	192.50
R09540A520	9.53	14.27	40%	Aluminium	2.00	2400 x 1200	64	9.38
R09540GB16	9.50	14.30	40%	Galvanised	1.60	2440 x 1220	26	23.08
R09540MS16	9.53	14.27	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R09540MS30	9.50	14.30	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R09540MS3074	9.50	14.27	40%	Mild Steel	3.00	2140 X 1070	19	31.58
R09540MS50	9.53	14.27	40%	Mild Steel	5.00	2400 x 1200	9	66.67
R09540MS60	9.50	14.30	40%	Mild Steel	6.00	2400 x 1200	7	85.71
R09540S415	9.50	14.30	40%	St/St 304	1.50	2440 x 1220	27	22.22
R09540S41563	9.50	14.30	40%	St/St 304	1.50	2440 x 1220	27	22.22
R09551A516	9.53	14.27	40%	St/St 304	1.50	1830 x 915	50	12.00
R09551GB10	9.50	12.70	51%	Aluminium	1.60	2400 x 1200	80	6.13
R09551GB12	9.50	12.70	51%	Galvanised	1.00	2440 x 1220	41	11.95
R09551GB16	9.50	12.70	51%	Galvanised	1.20	2440 x 1220	34	14.41
R09551MS10	9.50	12.70	51%	Galvanised	1.60	2440 x 1220	26	18.85
<b>R09551MS12</b>	9.50	12.70	51%	Mild Steel	1.00	2440 x 1220	43	11.40
R09551MS16	<b>9.50</b>	<b>12.70</b>	<b>51%</b>	<b>Mild Steel</b>	<b>1.20</b>	<b>2440 x 1220</b>	<b>36</b>	<b>13.61</b>
R12740MS60	9.50	12.70	51%	Mild Steel	1.60	2440 x 1220	27	18.15
R12748MS30	12.70	19.05	40%	Mild Steel	6.00	2400 x 1200	7	85.71
R12748MS60	12.70	17.46	48%	Mild Steel	3.00	2440 x 1220	14	37.14
R12749GB10	12.70	17.46	48%	Mild Steel	6.00	2400 x 1200	7	74.29
R12749GB16	12.70	17.27	49%	Galvanised	1.00	2440 x 1220	41	12.44
R12749MS16	12.70	17.27	49%	Galvanised	1.60	2440 x 1220	27	18.89
R12749MS30	12.70	17.27	49%	Mild Steel	1.60	2440 x 1220	27	18.89
R12749S415	12.70	17.27	49%	Mild Steel	3.00	2440 x 1220	14	36.43
R12749S41563	12.70	17.27	49%	St/St 304	1.50	2440 x 1220	27	18.89
R19151MS30	12.70	17.27	49%	St/St 304	1.50	1830 x 915	50	10.20
R25448MS30	12.70	17.27	49%	Mild Steel	3.00	2440 x 1220	14	35.00
	19.05	25.40	51%	Mild Steel	3.00	2440 x 1220	14	35.00
	25.40	35.00	48%	Mild Steel	3.00	2440 x 1220	15	34.67
<b>SQUARE HOLES</b>								
S04847MS0863	4.76S	6.99	47%	Mild Steel	0.80	1830 x 915	95	5.58
S05668MS0634	5.56 S	6.75	68%	Mild Steel	0.60	692 x 1219	100PACK	
S06469MS1064	6.35S	7.62	69%	Mild Steel	1.00	1830 x 1220	57	5.44
S07948A51083	7.94S	11.43S	48%	Aluminium	1.00	2400 x 900	165	3.15
S07948MS1	7.94S	11.43S	48%	Mild Steel	1.00	2440 x 1220	43	12.09
S08053A512	8.0 S	11.00	53%	Aluminium	1.20	2400 x 1200	107	4.39
S11144MS16	11.11 S	16.67S	44%	Mild Steel	1.60	2440 x 1220	27	20.74
S11149MS10	11.11S	15.88S	49%	Mild Steel	1.00	2440 x 1220	43	11.86

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
S11149MS16	11.11S	15.88S	49%	Mild Steel	1.60	2440 x 1220	27	18.89
S50046GB12	50.0 S	75.0S	46%	Galvanised	1.20	2440 x 1220	34	15.88
<b>DIAMOND HOLES</b>								
D05619MS08	5.56 D	12.7 S	19%	Mild Steel	0.80	2440 x 1220	53	15.28
D05619MS0863	5.56 D	12.7 S	19%	Mild Steel	0.80	1800 x 900	53	15.28
D05619MS0864	5.56 D	12.7 S	19%	Mild Steel	0.80	1800 X 1200	53	15.28
D05619MS0883	5.56D	12.7S	19%	Mild Steel	0.80	2400 x 900	53	15.28
D05619MS08C4	5.56 D	12.7 S	19%	Mild Steel	0.80	1 L/M X 1220	130	6.23 (l/m)
D50032A51283	50.0D	124	32%	Aluminium	1.20	2400 x 900	142	4.79
<b>CLUB &amp; ROUND - FANCY</b>								
F10236MS08	No 1 Fancy	15.24 S	36%	Mild Steel	0.80	2440 x 1220	53	12.08
F10236MS12	No 1 Fancy	15.24 S	36%	Mild Steel	1.20	2440 x 1220	36	17.78
F10236ZA0873	No 1 Fancy	15.24 S	36%	Zinc Anneal	0.80	2083 X 900	83	7.71
<b>HEXAGONAL HOLES</b>								
H09564MS12	9.53 H	11.89	64%	Mild Steel	1.20	2440 x 1220	36	10.00
<b>SLOTTED HOLES</b>								
L19141MS1063	19.05 x 3.18 EB:6.35,SB:4.83	22.23 code F	41%	Mild Steel	1.00	1800 x 900	76	7.76
L19141MS1083	19.05 x 3.18 EB:3.18,SB:3.18	22.23 code F	41%	Mild Steel	1.00	2400 x 900	57	10.35
L20337GB2064	20.3x7.62RES EB:5, SB:7.6	30.50 code F	37%	Galvanised	2.00	1830 X 1220	28	22.50
L25443AN1064 Anodised matt clear	25.4x6.35RES EB:6.35,SB:4.83	11.18 code A	43%	Aluminium	1.00	1800 X 1200	171	3.33
L25443MS10	25.4 x 6.35 EB:6.35,SB:4.83	11.18 code A	43%	Mild Steel	1.00	2440 x 1220	43	13.26
<b>SAFE -T- PERF</b>								
#J000	UNIVERSAL - 14		13%	Mild Steel	2.50	2440 X 1220	17	50.8
#J002	UNIVERSAL - 14		13%	H.D. GALV	2.50	2440 X 1220	17	55.0
#J010	UNIVERSAL - 14		13%	Mild Steel	2.50	2440x 915	22	38.1
#J012	UNIVERSAL - 14		13%	H.D. GALV	2.50	2440x 915	22	41.3
#J014	UNIVERSAL - 14		13%	St/St 304	2.00	2440x 915	27	31.8
#J015	UNIVERSAL - 14		13%	St/St 304	2.00	2440 X 1220	20	42.4
# B653	STOCK CRATE - 19		23%	Alum 5052	3.00	2400 x 1200	42	18.0
# B654	STOCK CRATE - 19		23%	Alum 5052	4.00	2400 x 1200	32	24.0
# B655	STOCK CRATE - 19		23%	Alum 5052	2.50	2400 x 900	68	11.26
# B656	STOCK CRATE - 19		23%	Alum 5052	2.50	2400 x 1200	51	15