

Stock Perforated Weights

This Technical Data Sheet provides the weights per sheet for Webforge Locker's stock perforated metal profiles

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
ACOUSTIC PATTERN								
R02411A50683	2.41	9.55	10%	Aluminium	0.55	2400 x 900	285	3.16
R02411A508	2.38	6.74	11%	Aluminium	0.80	2400 x 1200	160	5.56
R02411GB06	2.38	6.74	11%	Galvanised	0.55	2440 x 1220	75	11.87
R02411GB06103	2.38	6.74	11%	Galvanised	0.55	3050 x 915	80	11.13
R02411GB06104	2.38	6.74	11%	Galvanised	0.55	3050 x 1220	60	14.83
R02411GB06105	2.38	6.74	11%	Galvanised	0.55	3000 x 1500	49	18.16
R02411GB0663	2.38	6.74	11%	Galvanised	0.55	1830 x 915	133	6.69
R02411GB0664	2.38	6.74	11%	Galvanised	0.55	1830 x 1220	100	8.90
R02411GB0683	2.38	6.74	11%	Galvanised	0.55	2440 x 915	100	8.90
R02411GB0685	2.38	6.74	11%	Galvanised	0.55	2440 x 1500	61	14.59
R02411GB08	2.38	6.74	11%	Galvanised	0.80	2440 x 1220	52	17.12
R02411S406	2.38	6.74	11%	St/St 304	0.55	2440 x 1220	75	11.87
R02411ZA06	2.38	6.74	11%	Zinc Anneal	0.55	2440 x 1220	75	12.71
R02411ZA08	2.38	6.74	11%	Zinc Anneal	0.80	2440 x 1220	53	16.79
R03230A516	3.17	5.56	30%	Aluminium	1.6	2400 x 1200	80	8.74
R03230GB06	3.17	5.56	30%	Galvanised	0.55	2440 x 1220	75	9.33
R03230GB08	3.17	5.56	30%	Galvanised	0.8	2440 x 1220	51	13.57
R03230GB10	3.17	5.56	30%	Galvanised	1.00	2440 x 1220	41	16.96
R03230GB16	3.17	5.56	30%	Galvanised	1.60	2440 x 1220	26	27.14
R03230MS10	3.17	5.56	30%	Mild Steel	1.00	2440 x 1220	43	16.36
R03230MS16	3.17	5.56	30%	Mild Steel	1.6	2440 x 1220	27	26.17
R03230MS30	3.17	5.56	30%	Mild Steel	3.00	2440 x 1220	14	49.07
R03230S409	3.17	5.56	30%	St/St 304	0.9	2440 x 1220	46	15.34
R03230S415	3.17	5.56	30%	St/St 304	1.5	2440 x 1220	27	25.57
R03230ZA06	3.17	5.56	30%	Zinc Anneal	0.55	2440 x 1220	75	9.11
R03230ZA10	3.17	5.56	30%	Zinc Anneal	1.00	2440 x 1220	41	16.57
CLUB & ROUND HOLES								
F10236MS12	No 1 Fancy	15.24S	36%	Mild Steel	1.2	2440 x 1220	36	17.78

- This information is provided as a guide only in respect to Webforge Locker products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Webforge Locker endeavours to update this information and maintain the accuracy of its content, Webforge Locker cannot guarantee that the information provided is wholly comprehensive.

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
DIAMOND HOLES								
D05619MS08	5.56D	12.7S	19%	Mild Steel	0.8	2440 x 1220	53	15.28
D05619MS0883	5.56D	12.7S	19%	Mild Steel	0.8	2400 x 900	53	15.28
HEXAGONAL HOLES								
H09564MS12	9.53H	11.89	64%	Mild Steel	1.2	2440 x 1220	36	10.00
ROUND HOLES								
R01623MS12	1.60	3.20	23%	Mild Steel	1.20	2440 x 1220	36	21.39
R01636MS08	1.60	2.54	36%	Mild Steel	0.80	2440 x 1220	53	12.08
R01636S407	1.60	2.54	36%	St/St 304	0.70	2440 x 1220	59	10.85
R01637GB08	1.60	2.50	37%	Galvanised	0.80	2440 x 1220	52	12.12
R01637GB10	1.60	2.50	37%	Galvanised	1.00	2440 x 1220	41	15.37
R01637MS10	1.60	2.50	37%	Mild Steel	1.00	2440 x 1220	43	14.65
R01637ZS08	1.60	2.50	37%	Zinc Seal	0.80	2440 x 1220	53	11.89
R01637ZS0864	1.60	2.50	37%	Zinc Seal	0.80	1830 x 1220	70	9.00
R02036ZS06	1.95	3.10	36%	Zinc Seal	0.55	2440 x 1220	75	9.14
R02040GB10	2.00	3.00	40%	Galvanised	1.00	2440 x 1220	41	14.63
R02040MS10	2.00	3.00	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R02141S409	2.06	3.10	41%	St/St 304	0.90	2440 x 1220	46	12.83
R02141ZS05	2.06	3.10	41%	Zinc Seal	0.50	2440 x 1220	85	6.94
R02411A50683	2.41	9.55	10%	Aluminium	0.55	2400 x 900	285	3.16
R02411A508	2.38	6.74	11%	Aluminium	0.80	2400 x 1200	160	5.56
R02411GB06	2.38	6.74	11%	Galvanised	0.55	2440 x 1220	75	11.87
R02411GB06103	2.38	6.74	11%	Galvanised	0.55	3050 x 915	80	11.13
R02411GB06104	2.38	6.74	11%	Galvanised	0.55	3050 x 1220	60	14.83
R02411GB06105	2.38	6.74	11%	Galvanised	0.55	3000 x 1500	49	18.16
R02411GB0663	2.38	6.74	11%	Galvanised	0.55	1830 x 915	133	6.69
R02411GB0664	2.38	6.74	11%	Galvanised	0.55	1830 x 1220	100	8.90
R02411GB0683	2.38	6.74	11%	Galvanised	0.55	2440 x 915	100	8.90
R02411GB0685	2.38	6.74	11%	Galvanised	0.55	2440 x 1500	61	14.59
R02411GB08	2.38	6.74	11%	Galvanised	0.80	2440 x 1220	52	17.12
R02411S406	2.38	6.74	11%	St/St 304	0.55	2440 x 1220	75	11.87
R02411ZA06	2.38	6.74	11%	Zinc Anneal	0.55	2440 x 1220	75	12.71
R02411ZA08	2.38	6.74	11%	Zinc Anneal	0.80	2440 x 1220	53	16.79
R02440A510	2.41	3.66	40%	Aluminium	1.00	2400 x 1200	128	4.69
R02440GB10	2.38	3.57	40%	Galvanised	1.00	2440 x 1220	41	14.63
R02440GB16	2.38	3.57	40%	Galvanised	1.60	2440 x 1220	26	23.08
R02240MS10	2.38	3.57	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R02440MS16	2.38	3.57	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R02440S609	2.38	3.57	40%	St/St 316	0.90	2440 x 1220	46	13.04

- This information is provided as a guide only in respect to Webforge Locker products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Webforge Locker endeavours to update this information and maintain the accuracy of its content, Webforge Locker cannot guarantee that the information provided is wholly comprehensive.

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R03230A516	3.17	5.56	30%	Aluminium	1.60	2400 x 1200	80	8.75
R03230GB06	3.17	5.56	30%	Galvanised	0.55	2440 x 1220	70	10.00
R03230GB08	3.17	5.56	30%	Galvanised	0.8	2240 x 1220	51	13.73
R03230GB10	3.17	5.56	30%	Galvanised	1.00	2440 x 1220	41	17.07
R03230GB16	3.17	5.56	30%	Galvanised	1.60	2440 x 1220	26	26.92
R03230MS10	3.17	5.56	30%	Mild Steel	1.00	2440 x 1220	43	16.28
R03230MS16	3.17	5.56	30%	Mild Steel	1.60	2440 x 1220	27	25.93
R03230MS30	3.17	5.56	30%	Mild Steel	3.00	2440 x 1220	14	50.00
R03230S409	3.17	5.56	30%	St/St 304	0.90	2440 x 1220	46	15.22
R03230S415	3.17	5.56	30%	St/St 304	1.50	2440 x 1220	27	25.93
R03230ZA06	3.17	5.56	30%	Zinc Anneal	0.55	2440 x 1220	70	10.00
R03230ZA10	3.17	5.56	30%	Zinc Anneal	1.00	2440 x 1220	41	17.07
R03240GB06	3.17	4.76	40%	Galvanised	0.55	2440 x 1220	70	8.57
R03240GB08	3.17	4.76	40%	Galvanised	0.80	2440 x 1220	51	11.76
R03240GB10	3.17	4.76	40%	Galvanised	1.00	2440 x 1220	41	14.63
R03240GB16	3.17	4.76	40%	Galvanised	1.60	2440 x 1220	26	23.08
R03240MS08	3.17	4.76	40%	Mild Steel	0.80	2440 x 1220	53	11.32
R03240MS10	3.17	4.76	40%	Mild Steel	1.00	2440 x 1220	43	13.95
R03240MS12	3.17	4.76	40%	Mild Steel	1.20	2440 x 1220	36	16.67
R03240MS30	3.17	4.76	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R03240S415	3.17	4.76	40%	St/St 304	1.50	2440 x 1220	27	22.22
R03325MS30	3.25	6.10	25%	Mild Steel	3.00	2440 x 1220	14	53.57
R03341MS20	3.25	4.78	41%	Mild Steel	2.00	2440 x 1220	21	28.10
R03346MS10	3.25	4.52	46%	Mild Steel	1.00	2440 x 1220	43	12.56
R03346S409	3.25	4.52	46%	St/St 304	0.90	2440 x 1220	46	11.74
R04833MS16	4.76	7.92	33%	Mild Steel	1.60	2440 x 1220	27	24.81
R04851A510	4.76	6.35	51%	Aluminium	1.00	2400 x 1200	128	3.83
R04851A512	4.76	6.35	51%	Aluminium	1.20	2400 x 1200	107	4.58
R04851A516	4.76	6.35	51%	Aluminium	1.60	2400 x 1200	80	6.13
R04851A530	4.76	6.35	51%	Aluminium	3.00	2400 x 1200	43	11.47
R04851GB06	4.76	6.35	51%	Galvanised	0.55	2440 x 1220	70	7.00
R04851GB10	4.76	6.35	51%	Galvanised	1.00	2440 x 1220	41	11.95
R04851GB16	4.76	6.35	51%	Galvanised	1.60	2440 x 1220	26	18.85
R04851MS10	4.76	6.35	51%	Mild Steel	1.00	2440 x 1220	43	11.40
R04851MS12	4.76	6.35	51%	Mild Steel	1.20	2440 x 1220	36	13.61
R04851MS16	4.76	6.35	51%	Mild Steel	1.60	2440 x 1220	27	18.15
R04851MS20	4.76	6.35	51%	Mild Steel	2.00	2440 x 1220	22	22.27
R04851MS30	4.76	6.35	51%	Mild Steel	3.00	2440 x 1220	14	35.00
R04851MS3063	4.76	6.35	51%	Mild Steel	3.00	1830 x 915	25	19.60
R04851S409	4.76	6.35	51%	St/St 304	0.90	2440 x 1220	46	10.65

- This information is provided as a guide only in respect to Webforge Locker products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Webforge Locker endeavours to update this information and maintain the accuracy of its content, Webforge Locker cannot guarantee that the information provided is wholly comprehensive.

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R04851S415	4.76	6.35	51%	St/St 304	1.50	2440 x 1220	27	18.15
R04851S615	4.76	6.35	51%	St/St 316	1.50	2440 x 1220	27	18.15
R04851ZA10	4.76	6.35	51%	Zinc Anneal	1.00	2440 x 1220	43	11.40
R04851ZU10	4.76	6.35	51%	Zinc Alume	1.00	2440 x 1220	43	11.40
R06440A530	6.35	9.53	40%	Aluminium	3.00	2400 x 1200	43	14.05
R06440GB16	6.35	9.53	40%	Galvanised	1.60	2440 x 1220	26	23.08
R06440MS16	6.35	9.53	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R06440MS30	6.35	9.53	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R06440MS50	6.35	9.53	40%	Mild Steel	5.00	2400 x 1200	9	66.67
R06440S415	6.35	9.55	40%	St/St 304	1.50	2440 x 1220	27	22.22
R06440S41563	6.35	9.55	40%	St/St 304	1.50	1830 X 915	50	12.00
R06451A520	6.35	8.50	51%	Aluminium	2.00	2400 x 1200	64	7.66
R06451GB10	6.35	8.50	51%	Galvanised	1.00	2440 x 1220	41	11.95
R06451GB16	6.35	8.50	51%	Galvanised	1.60	2440 x 1220	26	18.85
R06451MS10	6.35	8.50	51%	Mild Steel	1.00	2440 x 1220	43	11.40
R06451MS12	6.35	8.50	51%	Mild Steel	1.20	2440 x 1220	36	13.61
R06451MS16	6.35	8.50	51%	Mild Steel	1.60	2440 x 1220	27	18.15
R06451S409	6.35	8.50	51%	St/St 304	0.90	2440 x 1220	46	10.65
R07962GB16	7.94	9.55	62%	Galvanised	1.60	2440 x 1220	26	14.62
R07962MS16	7.94	9.55	62%	Mild Steel	1.60	2440 x 1220	27	14.07
R07962MS20	7.94	9.55	62%	Mild Steel	2.00	2440 x 1220	21	18.10
R08047GB16	8.00	11.11	47%	Galvanised	1.60	2440 x 1220	26	20.38
R08047MS16	8.00	11.11	47%	Mild Steel	1.60	2440 x 1220	27	19.63
R08047MS30	8.00	11.11	47%	Mild Steel	3.00	2440 x 1220	14	37.86
R09540A520	9.53	14.27	40%	Aluminium	2.00	2400 x 1200	64	9.38
R09540GB16	9.50	14.30	40%	Galvanised	1.60	2440 x 1220	26	23.08
R09540MS16	9.53	14.27	40%	Mild Steel	1.60	2440 x 1220	27	22.22
R09540MS30	9.50	14.30	40%	Mild Steel	3.00	2440 x 1220	14	42.86
R09540MS50	9.53	14.27	40%	Mild Steel	5.00	2400 x 1200	9	66.67
R09540MS60	9.50	14.30	40%	Mild Steel	6.00	2400 x 1200	7	85.71
R09540S415	9.50	14.30	40%	St/St 304	1.50	2440 x 1220	27	22.22
R09551A516	9.50	12.70	51%	Aluminium	1.60	2400 x 1200	80	6.13
R09551A520	9.50	12.7	51%	Aluminium	2.00	2400 x 1200	64	7.65
R09551A530	9.5	12.7	51%	Aluminium	3.00	2400 x 1200	43	11.47
R09551GB10	9.50	12.70	51%	Galvanised	1.00	2440 x 1220	41	11.95

- This information is provided as a guide only in respect to Webforge Locker products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Webforge Locker endeavours to update this information and maintain the accuracy of its content, Webforge Locker cannot guarantee that the information provided is wholly comprehensive.

Part No.	Hole Size	Hole Pitch	Open Area	Material	Gauge	Size	No. Per Tonne - Pre Perf	Weight/Sheet (Kg) post-perf
R09551GB12	9.50	12.70	51%	Galvanised	1.20	2440 x 1220	34	14.41
R09551GB16	9.50	12.70	51%	Galvanised	1.60	2440 x 1220	26	18.85
R09551MS16	9.50	12.70	51%	Mild Steel	1.60	2440 x 1220	27	18.15
R12740MS60	12.70	19.05	40%	Mild Steel	6.00	2400 x 1200	7	85.71
R12749GB16	12.70	17.27	49%	Galvanised	1.60	2440 x 1220	27	18.89
R12749MS16	12.70	17.27	49%	Mild Steel	1.60	2440 x 1220	27	18.89
R12949S415	12.70	17.27	49%	St/St 304	1.50	2440 x 1220	27	18.89
R1915MS30	19.05	25.40	51%	Mild Steel	3.00	2440 x 1220	14	35.00
SAFE -T- PERF								
#J000	UNIVERSAL – 14		13%	Mild Steel	2.50	2440 X 1220	17	50.8
#J002	UNIVERSAL – 14		13%	H.D. GALV	2.50	2440 X 1220	17	55.0
#J015	UNIVERSAL – 14		13%	St/St 304	2.00	2440 X 1220	20	42.4
#B653	STOCK CRATE - 19		23%	Alum 5052	3.00	2400 x 1200	42	18.0
SLOTTED HOLES								
L25440A530	25.4 x 4.76 EB:4.76	19.04 Code E	40%	Aluminium	3.00	2400 x 1200	43	14.05
L25443MS10	25.4X6.35 EB:6.35,S B:4.83	11.18 Code A	43%	Mild Steel	1.00	2440 x 1220	43	13.26
SQUARE HOLES								
S07948MS10	7.94S	11.43S	48%	Mild Steel	1.00	2440 x 1220	43	12.09
S08053A512	8.0S	11.00	53%	Aluminium	1.20	2400 x 1200	107	4.39
S11149MS10	11.11S	15.88S	49%	Mild Steel	1.00	2440 x 1220	43	11.86
S11149MS16	11.11S	15.88S	49%	Mild Steel	1.60	2440 x 1220	27	18.89
S50046GB12	50.0S	75.0S	46%	Galvanised	1.20	2440 x 1220	34	15.88
DECORATIVE HOLES								
Aero	25.4, 28, 32.5	38	56%	Aluminium	3.00	2400 x 1200	43	10.30
Aztec	41 x 21	40 x 40.50	28%	Aluminium	3.00	2400 x 1200	43	16.86
Champagne	5, 8, 12, 15, 21	25	22%	Aluminium	3.00	2400 x 1200	43	18.26
Domino 358	3, 5, 8	10.25	25%	Aluminium	3.00	2400 x 1200	43	17.56
Ribbon	24 x 15	25	51%	Aluminium	3.00	2400 x 1200	43	11.47

- This information is provided as a guide only in respect to Webforge Locker products and intended applications.
- This information was prepared using Technical Data and market based experience available at the time of printing. While Webforge Locker endeavours to update this information and maintain the accuracy of its content, Webforge Locker cannot guarantee that the information provided is wholly comprehensive.